

«BAJUN» Projektiranje, proizvodnja i popravak aparata za zavarivanje

tel.: +385 (0)52 566-011 fax.: +385 (0)52 383-873

e-mail: bajun@pu.t-com.hr www.bajun.hr



| PROFESIONAL | | MIG/ MAG | MIG/ MAG | MIG/ MAG |
|-----------------|---------|-----------------------|-----------------------|-----------------------|
| MIG/MAG | | MB 260 (2R/4R) | MB 295 (2R/4R) | MB 390 (2R/4R) |
| | V AC | 3 x 400V | 3 x 400V | 3 x 400V |
| | Hz | 50-60 | 50-60 | 50-60 |
| | | 0,89 | 0,89 | 0,89 |
| OSIGURAČ | | 16A - tromi | 16A - tromi | 16A - tromi |
| | A | 40 – 260 (8°) | 40 – 295 (18°) | 40 – 390 (18°) |
| | V | 19 – 36 | 19 – 39 | 19 – 45 |
| | V | 16 - 27 | 16 – 29 | 16 – 33,5 |
| | A 50% | 260 | | |
| | A 60% | | 295 | 360 |
| | A 100% | 175 | 220 | 270 |
| | kVA max | 10 | 12 | |
| | A 100% | 8 | 10 | |
| | | K300 (16kg) | K300 (16kg) | K300 (16kg) |
| | mm | 0,6-0,8-1,0-1,2 | 0,6-0,8-1,0-1,2 | 0,6-0,8-1,0-1,2 |
| | | Fe – CrNi - Al | Fe – CrNi - Al | Fe – CrNi - Al |
| | kg | 77 | 84 | 105 |
| | cm | 78x39x65 | 78x39x65 | 78x39x65 |

IP IP23 **IC** H **EN** 60974-1



SVOJSTVA

TOČKASTO – UVLAČENJE ŽICE – SPORI START – 2T/4T - DOGORIJEVANJE



MIG260-MIG295-MIG390 PROFESIONAL



- PROFESIONAL
- IZVANREDNE KARAKTERISTIKE
- KOMPAKTAN
- ZAVARIVANJE ŽELJEZA, INOX-a I ALUMINIJA
- 2 ILI 4 POGONSKA VALJKA
- VISOKA INTERMITENCIJA RADA
- 2 GODINE GARANCIJE



OPREMA UKLJUČENA

| | MB 260 | MB295 | MB390 |
|----------------------|------------|------------|------------|
| 1. Polikabel | ERGO 25 3m | ERGO 36 4m | Ergo 36 4m |
| 2. Kabel za masu | 25 mmq 4m | 35 mmq 4m | 50 mmq 4m |
| 3. Redukcioni ventil | Ar/CO2 | Ar/CO2 | Ar/CO2 |